


MASKING FOR PLANE SURFACE

MASKING AND COVERING PRODUCTS FOR INDUSTRIAL SURFACE TREATMENT

PAINTING, POWDER COATING,
ELECTROPLATING, ANODIZING, ETC.




MADE IN CHINA

STANDARD

temperature range
up to **205 °C**

POLYESTER TAPE PC-21

- Polyester film / silicone adhesive
- Total thickness 0.08 mm
- Roll - 66 m (green color)
- Also offered on liner for die cutting
- No residue after removal




MADE IN CHINA

STANDARD

temperature range
up to **200 °C**

POLYESTER TAPE PC-22

- Polyester film / silicone adhesive
- Total thickness 0.06 mm
- Roll - 66 m (green color)
- Thinner performance
- Suitable for masking various shapes
- No residue after removal



MADE IN CHINA



STANDARD

temperature range
up to **200 °C**

POLYESTER TAPE PC-23



- Polyester film / silicone adhesive
- Total thickness 0.06 mm
- Roll - 33 m (transparent color)
- Thinner performance
- Suitable for masking various shapes
- No residue after removal

- ▶ Masking and covering products for industrial coatings (paint, powder coating, galvanizing, anodizing, etc.)
- ▶ Processing of masking tape according to your requirements
- ▶ Available in widths from 2 mm to 1000 mm (1 mm step)
- ▶ Coverage of the widest possible range of potential applications
- ▶ Most products in stock - almost immediate dispatch, no minimum order
- ▶ Possibility of delivery quantity according to your requirements and needs





POLYESTER TAPE SP-459

- Polyester film / silicone adhesive
- Total thickness 0,085 mm
- Roll - 66 m (blue color)
- Excellent adhesive / highest initial (TACK)
- Suitable for difficult flat surface condition that are rough, uneven, irregular texture finish
- No residue after removal





POLYESTER TAPE RD-714

- Modified polyester film / silicone adhesive
- Total thickness 0,16 mm
- Roll - 50 m (yellow color)
- Suitable for application where flexibility and high temperature resistance are critical
- Is preferred where multiple layers of coloured powder coating can be applied
- Minimal shrinkage, no residue after removal



DISCS ON SLIT LINER


- Modified polyester film / silicone adhesive
- Total thickness 0,08 mm (PC-21), 0,085 mm (SP-459)
- Slit back liner for easy removal
- No residue after removal



MASKING FOR PLANE SURFACE

MASKING AND COVERING PRODUCTS FOR INDUSTRIAL SURFACE TREATMENT

PAINTING, POWDER COATING,
ELECTROPLATING, ANODIZING, ETC.




MADE IN CHINA

STANDARD

temperature range
up to **250 °C**

POLYIMYDE TAPE PC - 44

- Polyimide film / silicone adhesive
- Total thickness 0,08 mm
- Roll - 33 m (amber color)
- Suitable for high temperature masking
- Recommended for electrical insulation
- Also offered on liner for die cutting
- No residue after removal




MADE IN EU

PREMIUM

temperature range
up to **300 °C**
for 1 hour

POLYIMYDE TAPE KAPTON®

- Polyimide film / silicone adhesive
- Total thickness 0,06 mm
- Roll - 33 m (amber color)
- Suitable for high temperature masking
- Recommended for electrical insulation
- Also offered on liner for die cutting
- No residue after removal



MADE IN USA

PREMIUM


temperature range
up to **260 °C**

SILICONE TAPES

- Self - fusing tape made of silicone rubber - without adhesive
- When wrapped with at least a 40% overlap upon it self, will cause a self - fusing bond, forming a airtight - waterproof seal
- High flexibility and ease of formability, roll - 11 m
- Excelent adhesion to masked surface
- Suitable for masking irregular shapes
- Resistant to chemicals, solvents, oils, acids, flame retardant
- Suitable for powder coating, electroplating, E-coating, insulating electrical connections


PRODUCT	WIDTH (mm)	THICKNESS (mm)	LENGHT (m)	PROFILE	COLOR	FLAME RETARDANT
1002536OR-R	6	0,256	11	rectangular	orange	
2005010OR-RB	12,5	0,508	3	rectangular	orange	
3010036GYFR-R	25	0,762	11	rectangular	grey	*
1515036CL-TB	38	0,381	11	triangular	clear	
3025036GYFR-R	63	0,762	11	rectangular	grey	*
2030036CL-TB	75	0,508	11	triangular	clear	
3040036GYFR-R	100	0,762	11	rectangular	grey	*

- ▶ Masking and covering products for industrial coatings (paint, powder coating, galvanizing, anodizing, etc.)
- ▶ Processing of masking tape according to your requirements
- ▶ Available in widths from 2 mm to 1000 mm (1 mm step)
- ▶ Coverage of the widest possible range of potential applications
- ▶ Most products in stock - almost immediate dispatch, no minimum order
- ▶ Possibility of delivery quantity according to your requirements and needs




GLASSCLOTH TAPE GC-500

- Glasscloth film / silicone adhesive
- Total thickness 0,18 mm
- Roll - 30 m (white color)
- Suitable for high temperature masking, blasting
- Good tearing and abrasion resistance
- No residue after removal




GLASSCLOTH TAPE LM-745

- 2 layer glasscloth laminate / silicone adhesive
- Total thickness 0,325 mm
- Roll - 33 m (white color)
- Suitable for plasma spray masking
- High abrasion and mechanical resistance
- Can resist harsh grit blasting processes
- No residue after removal



GLASSCLOTH TAPE LM-681

- 3 layer glasscloth laminate / silicone adhesive
- Total thickness 0,500 mm
- Roll - 33 m (white color)
- Suitable for HVOF and plasma spray masking
- Repair and rework of aircraft engine parts
- Very high abrasion and mechanical resistance
- Can resist harsh grit blasting processes




GLASSCLOTH TAPE LM-744

- Multiple layer glasscloth - copper laminate / silicone adhesive
- Total thickness 0,58 mm
- Roll - 33m (natural color)
- Suitable for HVOF and plasma spray masking
- Repair and rework of aircraft engine parts
- Very high abrasion and mechanical resistance
- Can resist harsh grit blasting processes

MASKING FOR PLANE SURFACE

MASKING AND COVERING PRODUCTS FOR INDUSTRIAL SURFACE TREATMENT

PAINTING, POWDER COATING,
ELECTROPLATING, ANODIZING, ETC.




MADE IN CHINA

STANDARD

temperature range
up to **90 °C**

PVC / VINYL TAPE BC-13

- PVC / rubber adhesive
- Total thickness 0.13 mm
- Roll - 33 m (black color)
- Thinner performance
- Suitable for masking various shapes
- Excellent resistance to abrasion, corrosion and moisture
- High adhesive and conformability
- Can resist blasting processes




MADE IN EU

PREMIUM

temperature range
up to **60 °C**

PVC / VINYL TAPE BC-14

- PVC / rubber adhesive
- Total thickness 0.16 mm
- Roll - 33 m (red color)
- Excellent resistance to abrasion, corrosion and moisture
- High adhesive and conformability
- Can resist blasting processes



MADE IN USA



PREMIUM

temperature range
up to **77 °C**

PVC / VINYL TAPE 3M-471



- Vinyl / rubber adhesive
- Total thickness 0.14 mm
- Roll - 33 m (blue color)
- Excellent resistance to abrasion, corrosion and moisture
- High adhesive and conformability
- Can resist blasting processes

- ▶ Masking and covering products for industrial coatings (paint, powder coating, galvanizing, anodizing, etc.)
- ▶ Processing of masking tape according to your requirements
- ▶ Available in widths from 2 mm to 1000 mm (1 mm step)
- ▶ Coverage of the widest possible range of potential applications
- ▶ Most products in stock - almost immediate dispatch, no minimum order
- ▶ Possibility of delivery quantity according to your requirements and needs



FABRIC TAPE DK-80

- Fabric film / caoutchouc adhesive
- Total thickness 0,23 mm
- Roll - 50 m (silver color)
- Suitable for sandblasting
- Excellent humidity and UV - resistancy



CREPE TAPE PM-120

- Crepe paper / rubber adhesive
- Total thickness 0.18 mm
- Roll - 50 m (cream color)
- Suitable for coating, powder coating, etc.
- Also offered on liner for die cutting





PEELABLE SILICONE RUBBER PM - 38

- Air - drying protective film coating type
- Packaging 30 ml or 90 ml (white color)
- One time use - all must be used at time of opening - cannot be reused
- Application by brush or dipping
- Cure time 24 hours
- Masking holes, axle, irregular surfaces and shapes
- Suitable for powder coating, plating operations, light sandblasting etc.
- Resistant to abrasion, bending, shaping
- Removal is done manually peeling

MASKING FOR PLANE SURFACE

MASKING AND COVERING PRODUCTS FOR INDUSTRIAL SURFACE TREATMENT

PAINTING, POWDER COATING,
ELECTROPLATING, ANODIZING, ETC.



U - PROFILES


- Material - SILICONE
- Re-usability
- Mask sheet-metal and profile edges to keep both sides of the edge uncoated
- Minimizes powder accumulations by it's shadow line
- Suitable for powder coating, electroplating, anodizing, etc.

PRODUCT	A (mm)	L (mm)
SU-010050	1,00	5,00
SU-010100	1,00	10,00
SU-012050	1,20	5,00
SU-012060	1,20	6,00
SU-015100	1,50	10,00
SU-015150	1,50	15,00
SU-020100	2,00	10,00

MADE IN CHINA

STANDARD

long-term application
up to **210 °C**
short-term application
up to **315 °C**



CLAMPING PROFILES

- Material - SILICONE
- Mask sheet-metal and profile edges to keep both sides of the edge uncoated
- By pushing the cord into the notch of the profile, the clamping force increases
- Re-usability
- Suitable for powder coating, electroplating, anodizing, etc.



PRODUCT	L (mm)
SPK-21006	13
SPK-21005/1	20
SPK-40702	30

MADE IN CHINA

STANDARD

long-term application
up to **210 °C**
short-term application
up to **315 °C**

- ▶ Masking and covering products for industrial coatings (paint, powder coating, galvanizing, anodizing, etc.)
- ▶ Processing of masking tape according to your requirements
- ▶ Available in widths from 2 mm to 1000 mm (1 mm step)
- ▶ Coverage of the widest possible range of potential applications
- ▶ Most products in stock - almost immediate dispatch, no minimum order
- ▶ Possibility of delivery quantity according to your requirements and needs



DISC ON SLIT LINER (PC-21)



- Polyester film / silicone adhesive
- Total thickness 0.08 mm
- Slit back liner for easy removal
- No residue after removal

PRODUCT	ø (mm)
PC-21-4	4
PC-21-5	5

PRODUCT	ø (mm)
PC-21-6	6
PC-21-10	10

PRODUCT	ø (mm)
PC-21-12	12
PC-21-15	15

PC-21-19	19
PC-21-21	21
PC-21-26	26



DISCS ON SLIT LINER (SP-459)

- Polyester film / silicone adhesive
- Total thickness 0,085 mm
- Excellent adhesive / highest initial (TACK)
- Suitable for difficult flat surface condition that are rough, uneven, irregular texture finish
- Slit back liner for easy removal
- No residue after removal

MASKING FOR PLANE SURFACE

MASKING AND COVERING PRODUCTS FOR INDUSTRIAL SURFACE TREATMENT

PAINTING, POWDER COATING,
ELECTROPLATING, ANODIZING, ETC.



CUSTOM DIE CUTS

- On the basis of masking tape (designed especially for powder coating)
- We cut from sheet: PC - 21, PC - 43, PC - 44, KAPTON®, BC - 12, PM - 120 and more...
- Cutouts we produced ourselves - can offer any shape or size
- Several different shapes can be produced together on one sheet (available at same time)
- Simply choose the type of masking film and send a sample, sketch or specification file
- The adhesive layer after heat leaves no adhesive residue



CUSTOM DIE CUTS - NON - STICK

- We cut from silicon, cork or magnetic sheet
- Can be applied using double-sided tape.
- Cutouts we produced ourselves - offered in any shape or size
- Simply choose the type of masking material and send a sample, sketch or specification file